

PROAG

ENGINEERED BY
MORRIS

BALE TITAN **RXR**



PRODUCTIVITY

Rolling rack provides faster loading and improved load stability

Can handle multiple sizes of bales and bundles for increased versatility

Larger tires result in less soil compaction

DURABILITY

154% stronger frame results in a longer product life

11% longer axle suspension creates a smoother ride

Increased load weight supports picking heavier bales

EASE of USE

ISOBUS terminal operating system allows use of existing tractor displays

Auto-greasing system simplifies maintenance

Low-maintenance sensors reduce down time

proagdesigns.com

BALE TITAN

Specifications and Options

Bale Length	6.5 ft - 8.5 ft (200 - 260 cm)
Bale Weight - Maximum	2,500 lbs (1,134 kg)
Loader Lift Capacity	5,000 lbs (2,268 kg)
Load Capacity - Maximum	24,000 lbs (10,886 kg)
Road-Siding Capacity	100 plus bales per hour
Tires - Standard	4 - 600/50R-22.5 16 ply
Weight - Stacker Empty	16,300 lbs (7,394 kg)
Tongue Weight Empty	1,300 lbs (590 kg)
Tongue Weight Loaded	2,500 lbs (1,134 kg)
Length for Shipping	28' 0" (853 cm) forks removed 28' 10" (879 cm) with forks
Overall Width	9' 10" (300 cm)
Transport Height - Empty with loader sitting on hitch	9' 4" (285 cm) without arm extensions and forks removed 12' 8" (386 cm) with arm extensions
Minimum height of building for stacking inside	22' (670 cm)
Hydraulic Brakes (Factory installed on both axles)	Optional
Work Light Kit	Optional
Mud Flap Kit	Optional
Rear Ballast Weight Kit - 1,200 lbs (544 kg)	Standard
Additional Rear Ballast Weight Kit - 300 lbs (136 kg)	Optional
Auto Lube System	Standard
Monitor System	Standard - ISO Terminal Optional - stand alone Raven CR7
Tractor - Horsepower	200 HP(150 kW) Minimum
- Weight	27,000 lbs (12,247 kg) Minimum
- Transmission	IVT, CVT, Power-Shift
- Hydraulic (Minimum requirements)	25 gpm (95 l/m) at 2,500 psi (17,237 kPa) Closed Center-Load Sense with low pressure drain line
- Drawbar	CAT 3 - (1 1/2" Diameter Draw Pin) or CAT 4 - (2" Diameter Draw Pin)
Bale Size - 3' x 3' Dry	18 - On or Off Strings
- 3' x 3' Wet	12 - On or Off Strings
- 3' x 4' Dry	12 - On Strings 8 - Off Strings
- 3' x 4' Wet	8 - Off Strings
- 4' x 4' Dry	8 - On or Off Strings
- 21 Pack Bundle	12 Bundles per Load (252 Small Square Bales)



CORPORATE OFFICE 205 - 2100 Airport Drive, Saskatoon, SK Canada S7L 6M6
p. 306.933.8585 f. 306.933.8626 Questions? email: info@morrisequipment.ca

The policy of MORRIS EQUIPMENT LTD. is one of continuing improvement; therefore, the company reserves the right to change any specification without notice.

Printed in Canada