

BALE TITAN RXR

Specifications and Options

Bale Length	6.5 ft - 8.5 ft (200 - 260 cm)
Bale Weight - Maximum	2,500 lbs (1134 kg)
Loader Lift Capacity	5,000 lbs (2268 kg)
Load Capacity - Maximum	24,000 lbs (10886 kg)
Road-Siding Capacity	100 plus bales per hour
Tires - Standard	4 - 600/50R-22.5 16 ply
Weight - Stacker Empty	16,300 lbs (7394 kg)
Tongue Weight Empty	1,300 lbs (590 kg)
Tongue Weight Loaded	2,500 lbs (1134 kg)
Length for Shipping	28' 0" (853 cm) forks removed 28' 10" (879 cm) with forks
Overall Width	9' 10" (300 cm)
Transport Height - Empty with loader sitting on hitch	9' 4" (285 cm) without arm extensions and forks removed 12' 8" (386 cm) with arm extensions
Minimum height of building for stacking inside	22' (670 cm)
Hydraulic Brakes (Factory installed on both axles)	Optional
Work Light Kit	Optional
Rear Ballast Weight Kit - 1200 lbs (544 kg)	Standard
Additional Rear Ballast Weight Kit - 300 lbs (136 kg)	Optional
Auto Lube System	Standard
Monitor System	Standard - ISO Terminal Optional - stand alone Raven CR7
Tractor - Horsepower	200 HP(150 kW) Minimum
- Weight	27,000 lbs (12247 kg) Minimum
- Transmission	IVT, CVT, Power-Shift
- Hydraulic (Minimum requirements)	25 gpm (95 l/m) at 2500 psi (17,237 kPa) Closed Center-Load Sense with low pressure drain line
- Drawbar	CAT 3 - (1 1/2" Diameter Draw Pin) or CAT 4 - (2" Diameter Draw Pin)
Bale Size - 3' x 3' Dry	18 - On or Off Strings
- 3' x 3' Wet	12 - On or Off Strings
- 3' x 4' Dry	12 - On Strings 8 - Off Strings
- 3' x 4' Wet	8 - Off Strings
- 4' x 4' Dry	8 - On or Off Strings
- 21 Pack Bundle	12 Bundles per Load (252 Small Square Bales)