

4SR PLUS AND 12SR PLUS BALE SKOOP

Specifications and Options

Model	4SR PLUS	12SR PLUS
Bale Length	6.5 ft - 8.5 ft (2 - 2.6 m)	6.5 ft - 8.5 ft (2 - 2.6 m)
Loader Lift Capacity	3,000 lbs (1,361 kg)	3,000 lbs (1,361 kg)
Load Capacity - Maximum	9,000 lbs (4,082 kg)	14,000 lbs (6,350 kg)
Road-Siding Capacity	40-60 tons/hour (36-54 tonnes)	40-60 tons/hour (36-54 tonnes)
Tires	2 - High Floatation - 600/50-22.5 16 ply	2 - High Floatation - 600/50-22.5 16 ply
Weight - Stacker Empty	7,000 lbs (3175 kg)	7,600 lbs (3447 kg)
Tongue Weight Empty	800 lbs (363 kg)	800 lbs (363 kg)
Tongue Weight Loaded	1,300 lbs (590 kg)	1,300 lbs (590 kg)
Length for Shipping	27 ft 10 in (8.49 m)	27 ft 10 in (8.49 m)
Overall Width	11 ft (3.35 m)	11 ft (3.35 m)
Transport Height Empty with loader sitting on hitch	8' 6" (2.59 m)	8' 6" (2.59 m)
Minimum height of building for stacking inside	19 ft (5.79 m)	19 ft (5.79 m)
Tractor - Horsepower	125 HP (92 kw) Minimum	125 HP (92 kw) Minimum
- Hydraulic	20 gpm (76 l/m) at 2250 psi (15,500 kPa) with 3 control valves	20 gpm (76 l/m) at 2250 psi (15,500 kPa) with 3 control valves
Bale Size - 2.5' x 4' Dry	7 - On Strings	-
- 3' x 3' Dry	-	12 - On Strings
* - 3' x 4' Dry	6 - On Strings	6 - On Strings
** - 4' x 4' Dry	4 - On or Off Strings	4 - On or Off Strings
- 21 Pack Bundle	4 Bundles per Load (84 Small Square Bales)	8 Bundles per Load (168 Small Square Bales)

* If you are going to pick up 3x4 or 4x 4 dry bales with the 12SR model - you need to disengage the Grab Hooks by turning valve #5 in 2 turns. Also, watch for the long alignment arms so they don't hit the stack as they will stick out longer than the bale. You want to open the alignment arms prior to backing into the stack so you don't knock the stack.

** If you are picking up only the 4x4 bales then you need to do the above - as well as remove the Bed Extensions by pulling out the pins, turn the bed extensions around, place the bed extensions in the storage position on the bed, and replace the pins.